



Print content with the name of the product

未注公差/General tolerances(mm)													0.1/10	
0 ~ 3	>3 ~ 6	>6 ~ 10	>10 ~ 18	>18 ~ 30	>30 ~ 50	>50 ~ 80	>80 ~ 120	>120 ~ 180	>180 ~ 250	>250 ~ 315	>315 ~ 400	>400 ~ 500		>500
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±2'

(Series No.) DT22M - FXD X / Y AC/DCZV

(Voltage grade):
AC/DC: 6/12/24/36/48/
110/220V
AC: 110/220/380V

(Color): RD: (Red)
GN: (Green)
YE: (Yellow)
WH: (White)
BU: (Blue)

(Contact form): 10: 1NO
01: 1NC
11: 1NO1NC

(Type of actuator): FRD: flat reset indicator
FLD: flat lock indicator

ITEM	NAME OF PART	MATERIAL	NOTES
4	Button head	/	/
3	Holding screw	/	/
2	Resistance module	/	/
1	Contact module	/	/

使用温度范围/Operating temperature(°C)	-25~+55(无冰冻)
使用湿度范围/Operating humidity(%RH)	45~85
接触电阻/Contact resistance(mΩ)	≤50
绝缘电阻/Insulation resistance(mΩ)	≥100
工频耐压/Power frequency withstand voltage	1890VAC/50Hz/60s
耐振动性/Vibration resistance	振幅约1.0mm/50Hz
耐冲击性/Shock resistance	>10g
机械寿命/Mechanical life	≥200万次
电气寿命/Electrical life	≥20万次
接线/Connection	螺钉连接, 线直径2x1.5mm 最大界限插片 6.3x0.8mm
符合RoHS环保要求/Conform to RoHS	Yes
标准颜色编号/Standard color number: PANTONE / RAL	/

DEGSON		MATERIAL:	SURFACE/COLOR:
APPD: 李根芳	2022.10.12	MAT NO./REV:	/ 00
CHKD: 马恩开	2022.10.12	MAT STATUS: 小批量	
DRFT: 马恩开	2022.10.12	NAME	
DT22M-FXD/X/Y/AC/DCZV			
DRAWING NO.	TYPE	DRAWING STATUS	SCALE
200118359	CUSTOMER DRAWING	work	1:1
SHEET		1/1	

REV	ECN	DESCRIPTION	DRFT	DATE
00		New Drawing	马恩开	2022.10.12