



公差/差/General tolerances(mm)	0.1/10
0	~
>3	~
>6	~
>10	~
>18	~
>30	~
>50	~
>80	~
>120	~
>180	~
>250	~
>315	~
>400	~
>500	~
>500	~
±0.12/±0.18/±0.22/±0.26/±0.31/±0.37/±0.57/±0.80/±0.93/±1.05/±1.15/±1.60/±2.20/±2.50	±7

please refer to the 3D model, for those unmarked dimensions

Note: The A&Z (H) in the name means: A(H) and Z(H).

ITEM	NAME OF PART	MATERIAL	NOTES
4	Screw	Steel	C3+Zn
3	Wire cage	Brass	Ni plated
2	Pin header	Copper	SnCo
1	Housing	PA66	UL94V-0

UL 标准/UL Standards:	B	C	D
额定电压/电流/Rated Voltage(V)/Current (A)	300/20	/	/
IEC 标准/IEC Standard:	/	/	/
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)	/	750/41	/
额定脉冲电压(KV)/Bare Impulse Voltage(KV)	4	4	4
螺丝扭矩/Torque Tightening (N·m/lb.in)	M4, 1.2/10.63		
线径范围(硬线和软线)/Wire Range (rigid and flexible) (AWG/mm²)	20~10/0.5~6.0		
线数范围/Pairs	N=01P		
使用温度范围/Operating temperature(°C)	-40~+105		
符合 RoHS 环保要求/Conform to RoHS	Yes		
标准颜色编号/Standard color number: PANTONE /RAL	XXXX / XXX		



APPR: 核准人	核准日期
CMOD: 审核人	审核日期
DRAFT: 设计人	设计日期
A4	(inch)

MATERIAL: /	SURFACE/COLOR: /
MAT NO./REV: /	MAT STATUS: /
DRAWING NO. 200057167	
TYPE CUSTOMER DRAWING	DRAWING STATUS /
SCALE 2:1	SHEET 1/1

REV	ECN	DESCRIPTION	DRAFT	DATE
00	/	/	/	/